



ENVIROGRID® SUBBASE SURFACE FOR LOAD SUPPORT

GEO PRODUCTS, LLC
12626 N. HOUSTON
ROSSLYN
HOUSTON, TX 77086
PHONE: (281) 820-5493
FAX: (281) 820-5499
www.geoproducts.org

NOTES:

1. DESIGN & INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH PROJECT SPECIFICATIONS.
2. SUGGESTED INFILL MATERIALS: ANGULAR ROCK, SANDY SOIL AND/OR NON-CLAY BASED SOIL, RECYCLED ASPHALT OR CONCRETE. (NOT LIMITED TO THESE)
3. FOR WET NATIVE SOIL TYPICAL SUB-BASE IS 6 TO 12 INCH OFF CLEAN STONE.
4. BASED ON THE APPLICATION, THE CELL DEPTH CAN BE 3", 4", 6" OR 8". (6" OR 8" FOR HEAVY LOADS)
5. CROWN IS NOT NEEDED. WATER WILL FLOW THROUGH ENVIROGRID.
6. DO NOT SCALE DRAWING.

| | |
|----------|--------------|
| DRAWN BY | MWJ |
| DATE | 6/2020 |
| REV. | - |
| SCALE | NOT TO SCALE |

